

KPM862

Boarding Pass and Bag Tag Kiosk Self-Service Printer

KPM862 Cutter AEA and Windows driver boarding pass and bag tag printer, autocutter with holding feature, CIS sensor, Ethernet, USB, RS232 interfaces.



EIGENSCHAFTEN

- Easy setting
- Barcode validity check
- Very fast and powerful
- Dot-saving function
- Manage large paper roll pulling
- Fanfold paper supported
- Full paper auto-loading without paper wasting
- CIS for notch/gap detection and “stock control” reading

FOCUS ON

- Veriprint® technology
- Compatible platforms: CUTE and CUPPS
- Firmware: Native AEA 2012 - 2022 support
- Emulation: ATB, BTP, GPP

APPLICATIONS

- Boarding passes and bag tags self-service kiosks

AVAILABLE MODELS

- Cutter
 - RFID
 - Dual feeder
-


ZUBEHÖR

- Power supply
 - Ejector
 - RFID module
 - Communication cable
 - Power cord
-

TECHNISCHES DATENBLATT


Printing Method	Thermal with fixed head
Resolution	203 dpi
Printing speed	high speed up to 300 mm/sec
Supported Barcode	1D and 2D IATA barcode printing: UPC-A, UPC-E, EAN13, EAN8, Code39, ITF, Codabar, Code93, Code128, Code32, PDF417, Data Matrix, Aztec, QRCode
Paper width	54 mm (according to IATA BTP specs - resolution 740) 82.5 mm (according to IATA ATB specs - resolution 722e)
Paper thickness	According to IATA specifications
Paper Roll Diameter	max. 150 mm (only for model with Dual Feeder)) max. 300 mm
Sensors	Head temperature, input paper presence, output paper presence, CIS reader, front and upper cover open, external low paper, tilting slide position (only for model with selector), dual feeder paper input (only for model with dual feeder)
Compatible platforms	CUTE and CUPPS
Firmware	Native AEA 2012 - 2022 support
Emulation	ATB, BTP, GPP
Interfaces	USB (or Virtual COM) RS232 Ethernet
Automatic cutter	Yes, total cut
Flash Memory	2 MB internal + 8 MB external
RAM Memory	640 KB internal + 8 MB external
Drivers	Windows® (32/64 bit); CUPS Linux (32/64 bit); Virtual COM (32/64 bit) with or without silent installation; Android™
Software Tools	PrinterSet
Power supply	Device: 24 Vdc±10% External power supply: Auto Range, 90-132 Vac & 190-264 Vac
Head Life	100Km / 100M pulses
Autocutter	1.000.000 cuts, total cut
Operating temperature	-20°C + 60°C
Dimensions	163.8 mm (L) x 152.5 mm (W) x 96.5 mm (H) (standard model); 256.6 mm (L) x 171 mm (W) x 104.5 mm (H) (model with ejector and dual feeder)
Weight	2.15 Kg (standard model); 3.55 Kg (model with ejector and dual feeder)

MODELLE



915LK010300700

PRINTER KPM862 CIS ETH USB
RS232 AVIATION



915LK010400700

PRINTER KPM862 CIS+DF ETH
USB RS232 AVIATION

Via Berettine, 2 - 43010 Fontevivo PR - UST-.ID: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - EINDEUTIGER CODE: 8RQN7AZ

Die technischen Daten auf dieser Website sind unverbindlich und können ohne vorherige Ankündigung geändert werden.

Letzte Aktualisierung: 14 März 2025