



K3

Elegant, practical and highly performing

With the new K3 printer Custom has reached the technological top in the table of POS and Retail printers. It is the ideal product to print receipts, coupons, kitchen orders, invoices and tickets. K3 is an elegant and highly performing product, designed and conceived to suit any and all environments: be it a luxury fashion shop, a fine restaurant or a large warehouse. K3 is equipped with an avant-garde technological package, WiFi module, application notes for Android and a special feature to print from Apple devices, like iPhone, iPodTouch and iPad. Using the product is further simplified by the illuminated tactile feed and cover opening buttons, so that K3 is intuitive and performing as soon as you start working on it. In addition, a LED will illuminate to indicate that servicing is required and when the paper roll is exhausted the cover mechanism will open automatically, thus prompting the user to quickly and easily replace it. K3 can be wall-mounted in vertical position. **K3 will render the experience at your venue unforgettable, from the first to the last moment.**



TECHNICAL SHEET

Printing Method	Thermal printing
Number of dots	8 dots / mm
Resolution	203 DPI
Printing (mm/sec)	350 mm/s
Auto-cutter	Cutter life 1 million cuts Total and partial cut
Character set	Standard font, Chinese 18030, Russian font
Numbers of columns	32 42 56
Characters	2.25 x 3 1.625 x 3 1.25 x 3 (L x H mm)-Normal
Supported Barcode	UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QRCODE, DATAMATRIX, PDF417, AZTEC
Paper width	58mm / 60mm / 80mm
Paper weight	from 55 to 90 gr/m ²
Roll Dimension	max Ø 100 mm
Sensors	Head temperature Paper presence Detection of black mark Cover open Low paper adjustable detection of black mark (optional) detection of black mark on non-thermal side (optional)
Emulation	CUSTOM/POS
Interfaces	RS232 / USB / ETHERNET
Flash Memory	4MB Flash SPI + 1MB internal to the micro
RAM Memory	64 MB
Data Buffer	16 kB
Drivers	Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); OPOS; JavaPOS; Android™; iOS
Software Tools	PrinterSet; Virtual COM, Custom Windows API
Power supply	24 Vdc ± 10%
Head Life	200 Km
Operating temperature	0°C + 50°C
Dimensions	206 mm (L) x 148 mm (W) x 140mm (H)
Weight	1.98 Kg

MODELS



911HM060200733

PRINTER K3 ETH USB RS232 USA

Via I. Newton, 4 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 05 February 2026