



D4 102

Impresora de Etiquetas

La D4 102 es una impresora de etiquetas de mesa compacta de 4" con características de nivel industrial y alto rendimiento. Múltiples puertos de comunicación, tecla multifunción y luz LED para trabajar cómodamente y mostrar el estado de error son algunas de las principales características que hacen que esta impresora sea ideal para aplicaciones de etiquetado.



FICHA TÉCNICA

	D4 102	D4 102 ETH
Processor		32bit RISC processor
Programming languages		EPL
Printing Method		Direct thermal / Thermal transfer
Resolution		203 dpi
Print speed		5 ips
Max. Print Length		3810 mm
Print Width		104 mm
Sensors	Moveable reflective sensor (movable from the center to the left side)	Cover open sensor Ribbon sensor
RAM Memory		64 MB SDRAM
Flash Memory		128 MB
Control Panel		1 multi-functional keys 6 status LED lights
Media		Maximum label width: 110 mm Minimum label width: 15 mm Maximum roll diameter: 127 mm Core diameter: 25.4 mm Media thickness: 0.06mm to 0.2mm Media type: Continuous, die-cut, tag, fan-f black mark
Ribbon		OD: 39 mm Max length: 100 m Width: 25.4 mm to 110 mm ID:12.7mm Ribbon type: Wax, wax/resin, resin
Emulation Language		PEPL, PDPL, PZPL
Interfaces	USB port Ethernet port 10/100 Mbps (option)	USB port Ethernet port 10/100 Mbps on board
Supported 1D/2D Barcodes	Code39 standard or extended, Code39 with check digit, Code93, Code128 UCC, Code128 a modes, Codabar, EAN8, EAN8/13 2&5 digit add-on, EAN13, Interleaved 2 of 5, Interleaved 2 check digit, Interleaved 2 of 5 with human readable check digit, UCC/EAN 128, UPC A, UPC add-on, UPC E, UPC E 2&5 digit add-on, UPC Interleaved 2 of 5, Code11 Data Matrix, MaxiCode, PDF417, QR code	
Fonts	5 internal expandable bitmap fonts (alpha-numeric) Downloadable soft font 4 directions: 0, 90, 180, 270 degrees 2 internal expandable bitmap fonts (numeric only)	
Drivers	Windows® (32/64 bit) – only on request WHQL and silent installation	
Image	PEPL: PCX, Direct binary graphic PDPL : PCX, BMP, HEX	
Options	Peeler kit Guillotine Cutter Ethernet module	
Power	Switching power adapter Input: 100 to 240 V, 1 .8 A, 50~60 Hz Output: 24 V, 2.5 A	

D4 102

D4 102 ETH

Environment

Operation: 5 °C to 45°C
Storage: -20 °C to 50 °C

Humidity

Operation: 10% to 90% non condensing
Storage: 5% to 95% non condensing

Dimensions

263 mm (L) × 200 mm (W) × 188 mm (H)

Weight

2 kg

MODELOS



911MK010100233

LABEL PRINTER D4 102 USB
BLACK



911MK010300J33

LABEL PRINTER D4 102 ETH USB
BLACK

Via Berettine, 2 - 43010 Fontevivo PR - N° IVA: IT02498250345 - TEL.: +39 0521 680111 - FAX: +39 0521 610701 - CÓDIGO ÚNICO: 8RQN7AZ

Los datos técnicos de este sitio no son vinculantes y pueden modificarse sin aviso previo.

Última actualización: 14 marzo 2025