



P-SCANRANGER

Presentación del escáner 1D/2D

P-SCANRANGER es un lector omnidireccional capaz de leer códigos 1D y 2D, también desde smartphones. Es un dispositivo extremadamente adaptable gracias a su estructura compacta que, sin embargo, no limita las prestaciones de lectura. El P-SCANRANGER tiene un rango de lectura especialmente amplio, de hasta 46° en horizontal y hasta 30° en vertical. Su cautivador diseño lo hace ideal para aplicaciones de venta al por menor.



ACCESORIOS

What is in the box:

- Device, USB-RJ45 cable, user manual, warranty card

FICHA TÉCNICA

Interface	HID USB / USB COM / RS232
Barcodes supported (1D)	UPC/EAN/ (UPCA/UPCE/UPCE 1 /EAN-8/EAN-I 3/ JAN-8/ JAN- I 3 plus supplemental, ISBN, ISSN, Coupon Code), Code 39, Code 39 Full ASCII, Trioptic, Code 32 (Italian Pharmacode), Code 128 (Standard, Full ASCII, UCC/EAN-128, ISBT-128 Concatenated), Code 93, Codebar/NW7, Interleaved 2 of 5, Discrete 2 of 5, IATA, Chinese 2 of 5, Matrix 2 of 5, Code 11), MSI Plessey, GSI DataBar, (Omnidirectional, Truncated, Stacked, Stacked Ominidirectional, Limited, Expanded, Expanded Stacked)
Barcodes supported (2D)	PDF417 (Variant, Standard, Macro), MicroPDF417 (Standard, Macro), Composite Codes (CC-A, CC-B, CC-C), MaxiCode, Data Matrix, Data Matrix Inverse, QR Code, QR Inverse, Micro QR Code, Aztec Code, Aztec Inverse, U.S. Posnet and Planet, U.K. Post, Japan Post, Australian Post, Netherlands KIX Code, Royal Mail 4 State Customer, UPU FICS 4 State Postal, USPS 4CB
OPTICAL	
Optical system	752 (H) × 480 (V) pixels (Wide VGA)
Light source	Aiming pattern: single dot, 625 nm LED
Resolution	4 mil (CODE 39), 7.5 mil (Data Matrix), 5 mil (PDF417)
Field of view	Horizontal: 46.1°, Vertical 30.4°
Indicator	Beeper and LED
Reading distance	Up to 267 mm
ELECTRICAL	
Voltage	DC 5V
ENVIRONMENT	
Operating temperature	0 °C to 40 °C
Drop	1.5 m drops
PHYSICAL	
Weight	300 g w/cable
Dimensions	73 mm (W) x 140 mm (H) x 70 mm (D)

Via I. Newton, 4 - 43010 Fontevivo PR - N° IVA: IT02498250345 - TEL.: +39 0521 680111 - FAX: - CÓDIGO ÚNICO: 8RQN7AZ

Los datos técnicos de este sitio no son vinculantes y pueden modificarse sin aviso previo.

Última actualización: 18 marzo 2026