



## P-SCANRANGER

### Lecteur code-barres de présentation 1D/2D

P-SCANRANGER est un lecteur omnidirectionnel en mesure de lire des codes 1D et 2D, sur smartphone aussi. Il s'agit d'un dispositif extrêmement adaptable grâce à sa structure compacte qui ne limite toutefois pas les performances de lecture. P-SCANRANGER dispose d'une plage de lecture très vaste, jusqu'à 46° à l'horizontale et jusqu'à 30° à la verticale. Son design captivant en fait une solution idéale pour des applications dans le secteur de la vente au détail.



### ACCESSOIRES

#### What is in the box:

- Device, USB-RJ45 cable, user manual, warranty card

## FICHE TECHNIQUE

<b>Interface</b>	HID USB / USB COM / RS232
<b>Barcodes supported (1D)</b>	UPC/EAN/ (UPCA/UPCE/UPCE 1 /EAN-8/EAN-I 3/ JAN-8/ JAN- I 3 plus supplemental, ISBN, ISSN, Coupon Code), Code 39, Code 39 Full ASCII, Trioptic, Code 32 (Italian Pharmacode), Code 128 (Standard, Full ASCII, UCC/EAN-128, ISBT-128 Concatenated), Code 93, Codebar/NW7, Interleaved 2 of 5, Discrete 2 of 5, IATA, Chinese 2 of 5, Matrix 2 of 5, Code 11), MSI Plessey, GSI DataBar, (Omnidirectional, Truncated, Stacked, Stacked Ominidirectional, Limited, Expanded, Expanded Stacked)
<b>Barcodes supported (2D)</b>	PDF417 (Variant, Standard, Macro), MicroPDF417 (Standard, Macro), Composite Codes (CC-A, CC-B, CC-C), MaxiCode, Data Matrix, Data Matrix Inverse, QR Code, QR Inverse, Micro QR Code, Aztec Code, Aztec Inverse, U.S. Posnet and Planet, U.K. Post, Japan Post, Australian Post, Netherlands KIX Code, Royal Mail 4 State Customer, UPU FICS 4 State Postal, USPS 4CB
<b>OPTICAL</b>	
<b>Optical system</b>	752 (H) × 480 (V) pixels (Wide VGA)
<b>Light source</b>	Aiming pattern: single dot, 625 nm LED
<b>Resolution</b>	4 mil (CODE 39), 7.5 mil (Data Matrix), 5 mil (PDF417)
<b>Field of view</b>	Horizontal: 46.1°, Vertical 30.4°
<b>Indicator</b>	Beeper and LED
<b>Reading distance</b>	Up to 267 mm
<b>ELECTRICAL</b>	
<b>Voltage</b>	DC 5V
<b>ENVIRONMENT</b>	
<b>Operating temperature</b>	0 °C to 40 °C
<b>Drop</b>	1.5 m drops
<b>PHYSICAL</b>	
<b>Weight</b>	300 g w/cable
<b>Dimensions</b>	73 mm (W) x 140 mm (H) x 70 mm (D)

Via I. Newton, 4 - 43010 Fontevivo PR - NUMÉRO DE TVA : IT02498250345 - TÉL : +39 0521 680111 - FAX : - CODE UNIVOQUE: 8RQN7AZ

Les données techniques de ce site ne sont pas contraignantes et peuvent être modifiées sans préavis.

Dernière mise à jour : 18 mars 2026