



TG1260HIII

60mm ticket / receipt printer

- Metal frame (galvanized/aluminium alloy)
- High print quality (200 DPI)
- Paper width: 60mm
- Paper thickness: from 60 to 80 μ m
- Printing > 60 mm/sec
- RS232 and USB interfaces
- It prints 1D and 2D barcodes (QR CODE)
- Characters: European, International, Portuguese, Nordic, Arabic, Chinese and Russian
- Highly reliable cutter: over 1,000,000 cuts
- Sensors: head temperature, paper presence, anti paper jamming, ticket collection, paper end and near paper end



CARACTERÍSTICAS

- Zero power consumption in stand by mode
- Patented Anti Jamming System
- Suitable for tough environments, down to -20°C up to +70°C
- Illuminated paper bezel
- Multi-position paper roll
- Large paper roll: Ø 100 mm
- Metal structure that provides increased rigidity for the printing mechanism and facilitates motor heat dissipation, resulting in improved stability and reliability over time
- Improved distribution of the head-roller pressure, resulting in improved printing quality


APPLICATIONS

- Self-service kiosks
 - Banking machines
 - Gaming machines
 - Parking meters
 - Queue management systems
 - Vending machines
-

FICHA TÉCNICA

| | |
|------------------------|--|
| Printing Method | Thermal with fixed head |
| Number of dots | 8 dots/mm |
| Columns | 32 - 42 - 56 |
| Resolution | 203 DPI |
| Printing (mm/sec) | 60 mm/sec |
| Character set | PC437, PC850, PC860, PC863, PC865, PC858, PC866, GB2312 |
| Printing Format | Normal, height and width from 1 to 4, bold, negative, underlined, script, italic |
| Printing Direction | Straight, 180° |
| Paper width | 60 mm |
| Paper weight | from 55 to 70 g/m ² |
| Paper thickness | from 60 to 80 μ m |
| Roll Dimension | 100 mm |
| Sensors | Head temperature, paper jamming, paper presence, notch presence, optional: almost external paper end |
| Emulation | Custom/POS, TGH |
| Interfaces | RS232 + USB |
| Data Buffer | 2 kB |
| Flash Memory | 4 MB |
| Graphic Memory | 2 logos of 448x584 dots |
| Drivers | Windows® (32/64 bits) – apenas a pedido WHQL e instalação silenciosa; Linux (32/64 bits); COM virtual (Linux ou Windows 32/64 bits); Android™ |
| Software Tools | Status Monitor, PrinterSet, CustomPowerTool, Custom Windows API |
| Power supply | 12V +/- 10% |
| Medium consumption | 0.66A (12.5% dots turned on) |
| MTBF | 420,000 hours (electronic board) |
| Head Life | 50Km/100M pulses |
| Operating temperature | -20°C + 70°C |
| Dimensions | 135 mm (C) x 114 mm (L) x 81 (A) |
| Weight | 0.6 Kg |

MODELOS



915CD090100300

PRINTER TG1260HIII USB CUTTER
LED OUT

Via Berettine, 2 - 43010 Fontevivo PR - P. IVA: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - CÓDIGO UNÍVOCO: 8RQN7AZ

As informações técnicas neste site não são vinculadas e podem ser alteradas sem aviso prévio.

Última atualização: 14 março 2025