




## VKP60

### 60mm Ultra-Compact Receipt/Ticket Kiosk Printer

VKP60 is the kiosk printer for **receipt and ticket** printing. Thanks to its **multiple configurations**, it is suitable for a wide variety of self-service applications. Compact, versatile, and provided with useful features such as **anti-jamming**, **full and partial cutting**, this device can be employed in any type of kiosk thanks to its adjustable two-position roll holder. VKP60 is available in three different configurations: **compact**, **paper mouth** and **presenter**.




## ACCESORII

- Roll holder bracket VKP60 with NPE
- Roll holder bracket wireless VKP60 Compact
- Roll holder bracket wireless VKP60 Presenter
- Roll holder bracket VKP60 Presenter with NPE
- Wireless roll holder VKP60
- VKP60 adapter to 12Vdc
- VKP60 compatible TG2460 fixing kit
- Dongle ETH VKP60
- Dongle RS232 VKP60
- Power supply 24V 60W connector DIN


## FI?? TEHNIC?

|                       | VKP60 - Compact                                                                                                                                                                         | VKP60 - Paper Mouth                   | VKP60 - Presenter                                                                                                    |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Resolution            | 203 dpi                                                                                                                                                                                 |                                       |                                                                                                                      |
| Power supply          | 24V, 12V adapter (optional)                                                                                                                                                             |                                       |                                                                                                                      |
| Printing speed        | up to 200 mm/s @24V                                                                                                                                                                     |                                       |                                                                                                                      |
| Paper thickness       | 50 - 130 μm                                                                                                                                                                             |                                       | 50 - 100 μm                                                                                                          |
| Roll diameter         | max. 100 mm (with CUSTOM roll holder)                                                                                                                                                   |                                       |                                                                                                                      |
| Paper width           | 44, 50, 54, 58, 60 mm                                                                                                                                                                   |                                       |                                                                                                                      |
| Cutter                | Total and partial cut                                                                                                                                                                   |                                       | Total cut                                                                                                            |
| Interfaces            | USB 2.0, Virtual Com, RS232 or ETH (optional)                                                                                                                                           |                                       |                                                                                                                      |
| Sensors               | Paper present, cover open, printhead temperature, cutter home, black mark, anti-jam, optional: near paper end                                                                           |                                       | Paper present, cover open, printhead temperature, cutter home, black mark, paper in output, optional: near paper end |
| Character set         | PC437, PC850, PC858, PC860, PC862, PC863, PC864, PC865, PC866, Katakana, WPC1250, WPC1251, WPC1252, WPC1253, WPC1254, WPC1255, WPC1256, WPC1257, WPC1258, Chinese GB18030, Korean PC949 |                                       |                                                                                                                      |
| Supported barcodes    | UPC-A - UPC-E - EAN13 - EAN8 - CODE39 - ITF - CODABAR - CODE93 - CODE128 - CODE32<br>Codice QR - Aztec - PDF417 - Datamatrix - GS1 Databar                                              |                                       |                                                                                                                      |
| Print head life       | 200 km / 100M pulses                                                                                                                                                                    |                                       |                                                                                                                      |
| Cutter life           | 1M                                                                                                                                                                                      |                                       |                                                                                                                      |
| LED paper mouth       | No                                                                                                                                                                                      | Default                               |                                                                                                                      |
| Drivers               | Windows® (32/64 bit), CUPS Linux (32/64 bit), OPOS, Java POS, Status Monitor SDK                                                                                                        |                                       |                                                                                                                      |
| SW tools              | PrinterSet, CPT, Windows® API, Driver Manager, Android™ API, iOS API                                                                                                                    |                                       |                                                                                                                      |
| Operative temperature | -20 to +70°C ; 10 to 90% RH (no condensation)                                                                                                                                           |                                       |                                                                                                                      |
| Dimensions            | 86 mm (W) x 58 mm (D) x 81 mm (H)                                                                                                                                                       | 86 mm (W) x 78.5 mm (D) x 89.5 mm (H) | 109.8 mm (W) x 99 mm (D) x 87.3 mm (H)                                                                               |
| Weight                | 330 g                                                                                                                                                                                   | 340 g                                 | 453 g                                                                                                                |


## MODELE

**915NA010100300**

PRINTER VKP60 USB RS232  
COMPACT

**915NA020100300**

PRINTER VKP60 USB RS232  
PAPER MOUTH

**915NA030100300**

PRINTER VKP60 USB RS232  
PRESENTER

---

Via Berettine, 2 - 43010 Fontevivo PR - TVA: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - COD UNIC: 8RQN7AZ

Datele tehnice de pe acest site nu sunt obligatorii și pot fi modificate fără nicio notificare.

Ultima actualizare: 15 septembrie 2025