

??????????????

- 300 dpi
- ,
-
- Dot Danneggiati: ,
- 100%- Ethernet
-
-
-

??????????

-
-
-
-
- -
-
-
- /

?????????? ??????

- +USB+Ethernet 200 dpi 24V
- +USB+Ethernet 300 dpi 24V

??????????

??? ? ???????:

- , +

???????????? ???? ?????

?????? ? 200 dpi	?????? ? 300 dpi
XXXXXXXXXX	XXXXXXXXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXXXXXX 8 XXXXX/XX	12 XXXXX/XX
XXXXXXXXXXXXXXXXXXXX 203 dpi	300 dpi
XXXXXXXXXX XXXXXXXX (XX/XX)	200 XX/XX
XXXXXXXXXXXXXXXXXXXX	PC437, PC850, PC860, PC863, PC865, XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXX-XXXX	1D X2D
XXXXXXXXXXXXXXXXXXXX	XXXXXXXXXX, 1x 8x X XXXXXXXX X XXXXXXXX, XXXXXXXXXXXXXXXXXXXX, XXXXXXXXXXXXXXXXXXXX, XXXXXXX, X
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	XXXXXXXX, 90°, 180°, 270°
XXXXXXXXXXXXXXXXXXXX	210 XX/ 216 XX (A4" - US - XXXXX)
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	XX 58 XX 78 XX/XX ²
XXXXXXXXXXXXXXXXXXXX	XX 63 XX 85 XX
XXXXXXXXXXXXXXXXXXXX	Ø 180XX XXXXX
XXXXXXXXXXXX	CUSTOM/POS
XXXXXXXXXXXXXXXXXXXX	RS232 + USB (XXXX XXXXXXXXXXXXXXXXXXXX COM) + Ethernet
XXXXXXXXXXXXXXXXXXXX	19 XX
XXXXX-XXXXXX	2MB internal flash and 8MB external SPI flash
XXXXXXXXXXXX RAM	128Kbytes
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	5 XXXXXXXXXXXX 1600 x 327 XXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	5 XXXXXXXXXXXX 2368 x 327 XXXXXXX
XXXXXXXXXXXX	Windows® (32/64 XXXX) — XXXXXXXX XX XXXXXXXXXXXX WHQL X XXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXX; Linux (32/64 XXXX); Android™; iOS
XXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXX X XXXXXXXXXXXX	Set, CustomPowerTool, Status Monitor, Custom Windows API
XXXXXXXXXXXX	24 Vdc ± 10%
CXXXXXXXXXXXXXXXXXXXXXXXXXXXX	2.5A (12,5% XXXXXXXXXXXXXXXXXXXX)
XXXXX XXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX XXXXXXX	100XX/100M XXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	300.000 XXXXXXXXXXXXXXX
XXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX	0°C + 50°C
XXXXXXXXXXXX	270 x 190 x 90 XX
XXXX	4.8 XX

??????

