



## D4 302-K

### Label Printer

D4 302-K is a compact size 4" desktop label printer with a industrial level equipments and high performance. D4 302-K is equipped with a colorful backlight LCD with clear image display that makes the menu friendly to users and it is also provided with a built in multi functional keyboard, being suitably used in confined space. Multiple communication ports, 19 buttons keyboard, SD slot for the data storage, real time clock for time and date printing application are some of the main features that makes this label printer ideal for all range of application.



????

<b>Printing Method</b>	Direct thermal / Thermal transfer
<b>Resolution</b>	203 dpi
<b>Printing speed</b>	5 ips
<b>Max. Print Length</b>	3810 mm
<b>Max. Print Width</b>	104 mm
<b>Sensors</b>	Moveable see-through and reflective sensor Ribbon sensor Cover open sensor
<b>RAM Memory</b>	128 MB
<b>Display</b>	Colorful 2.8" backlight LCD display, 240 × 320 dots
<b>Control Panel</b>	19 multi-functional keys
<b>Media</b>	Maximum label width: 110 mm Minimum label width: 15 mm Maximum roll diameter: 127 mm Core diameter: 25.4 mm Media thickness: 0.06 mm to 0.2 mm Media type: Continuous, die-cut, tag, fan-fold, black mark
<b>Ribbon</b>	OD: 39 mm Max length: 100 m Width: 25.4 mm to 110 mm ID: 12.7 mm Ribbon type: Wax, wax/resin, resin
<b>Emulation Language</b>	PEPL, PDPL, PZPL
<b>Interfaces</b>	USB port USB master port Serial port RS-232 Option: Ethernet port 10/100Mbps
<b>Supported 1D/2D Barcodes</b>	Code39 stand or extended, Code39 with check digit, Code93, Code128 UCC, Code128 Auto A,B,C mode, EAN8, EAN8/13 2&5 digit add-on, EAN13, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Interleaved with human readable check digit, UCC/EAN 128, UPC-A, UPC-A 2&5 digit add-on, UPC-E, UPC-E 2&5 digit add-on, UPC Interleaved 2 of 5, Code 11 PDF417, Maxicode, Data Matrix, QR code
<b>Fonts</b>	5 internal expandable bitmap fonts (alpha-numeric) 2 internal expandable bitmap fonts (numeric only) Downloadable soft font 4 directions: 0, 90, 180, 270 degrees
<b>Image</b>	PEPL: PCX, Direct binary graphic PDPL: PCX, BMP, HEX
<b>Options</b>	Peeler kit Cutter Ethernet module
<b>Power</b>	Switching power adapter Input: 100 to 240 V, 1.8 A, 50~60 Hz Output: 24 V, 2.5 A
<b>Audio</b>	Beep sound when error occurs
<b>Environment</b>	Operation: 5 °C to 45 °C Storage: -20 °C to 50 °C
<b>Humidity</b>	Operation: 10% to 90% non condensing Storage: 5% to 95% non condensing

**Dimensions** 263 mm (L) × 200 mm (W) × 188 mm (H)

---

**Weight** 2 kg

---

??



**911MK030100333**

LABEL PRINTER D4 302-K USB  
RS232 WITH KEYBOARD AND  
DISPLAY BLACK

---

Via Berettine, 2 - 43010 Fontevivo PR -

IT02498250345 -

+39 0521 680111 -

+39 0521 610701 -

8RQN7AZ

14 2025