



TG2480HIII


/ 80

- /
- 200 dpi
- 80
- : 63 85 mm
- > 150 /
- RS232 USB
- : UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QR CODE
- : 1.000.000
- :
- , , , ,



??

-



??

- Kiosk
 -
-

??

?????????

- 2
-

????

????

8 /
43 - 60 - 76
203 dpi
/ 150 /
PC437, PC850. PC860. PC863, PC865, PC858, PC866, GB2312
1 4
, 180°
80
55 80 / ²
63 85
90
, , , ,
Custom/POS, TGH
RS232 + USB
2 kB
1 MB
2 608x430
Windows® 32/64 --- WHQL
Linux 32/64
COM Linux Windows 32/64
OPOS
, PrinterSet, CustomPowerTool, Custom Windows API
24V +/- 10%
0.8A (12,5%)
MTBF 450.000 ()
50 /100M
0°C + 50°C
130,2 mm (W) x 271,5 mm (D) x 102 mm (H)
1130

??



915CH030100300
PRINTER TG2480HIII USB RS232

Via I. Newton, 4 - 43010 Fontevivo PR - IT02498250345 - +39 0521 680111 - - 8RQN7AZ

18 2026