



TL60III

/ 60

- /
- 200 dpi
- 60
- : 63 85 mm
- > 140 /
- RS232 USB
- : UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QRCODE
- :
- : 1.000.000
- :



??

- : 77
- , -20°C +70°C
- :
- 80
-

??

- Kiosk
-

??
????????

•	
????	
????	
8	/
24 - 32 - 44	
203 dpi	
/	140 /
PC437, PC850. PC860. PC863, PC865, PC858, PC866, VISCII(0104:PC437, PC850. PC860. PC863, PC865, PC858, GB2312)	
1 4	
, 180°	
60	
55 80 / ²	
63 85	
80	
Custom/POS, TGH	
RS232 + USB	
2 kB	
1 MB	
2 448x584	
Windows® 32/64 — WHQL	
Linux 32/64	
COM Linux Windows 32/64	
TM	
Status Monitor, PrinterSet, CustomPowerTool, Custom Windows API	
24V +/- 10%	
0.65A (12,5%)	
MTBF	172.000 ()
50 /100M	
TL60III /	
TL60III EJ	
-20°C + 70°C	
130(l)x105(w)x77(h)	
0.800	

??

**915CJ040100300**

PRINTER TL60III USB RS232

**915CJ040200300**

PRINTER TL60III USB RS232
EJECTOR

Via I. Newton, 4 - 43010 Fontevivo PR -

IT02498250345 -

+39 0521 680111 -

-

8RQN7AZ

18 2026