



TL80III

/ 80

- /
- 200 dpi
- 80
- : 63 85 mm
- > 140 /
- RS232 USB
- : UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QRCODE
- :
- : 1.000.000
- :



??

- : 77
- , -20°C +70°C
- :
- 90
-

??

- Kiosk
- Kioski
-

??
????????

•	
????	
????	
8	/
33 - 43 - 60	
203 dpi	
/	140 /
PC437, PC850. PC860. PC863, PC865, PC858, PC866, VISCII(0104:PC437, PC850. PC860. PC863, PC865, PC858, GB2312)	
1 4	
, 180°	
80	
55 80 / ²	
63 85	
90	
Custom/POS, TGH	
RS232 + USB	
2 kB	
1 MB	
2 608x430	
Windows® 32/64 --- WHQL	
Linux 32/64	
COM Linux Windows 32/64	
™	
Status Monitor, PrinterSet, CustomPowerTool, Custom Windows API	
24V +/- 10%	
0.8A (12,5%)	
MTBF	172.000 ()
50 /100M	
MCBF	1.000.000
-20°C + 70°C	
128,7(L)x130.2(W)x77(H)	
0.900	

??



915CK030100300
PRINTER TL80III USB RS232

Via Berettine, 2 - 43010 Fontevivo PR - IT02498250345 - +39 0521 680111 - +39 0521 610701 - 8RQN7AZ

30 2025